

# CHRIS WITOR.com

## VARIOUS REAR SHOCK MOUNTING CENTRES:

Make	(open) Droop inches	(open) Droop mm	(closed) Bump inches	(closed) Bump mm
Leda my spec Bespoke	18.250	463.550	14.000	355.600
CWAVO1420K	20.000	508.000	14.000	355.600
Monroe R3255	20.125	511.175	15.000	381.000
Sachs SA961001	20.500	520.700	13.500	342.900
Armstrong	20.500	520.700	15.000	381.000
SPAX TAG1119-1	20.708	526.000	14.330	364.000
Sachs/Boge Automatic	20.750	527.050	13.625	346.075
XRN Budget	20.750	527.500	13.875	365.125
KYB 554017	20.750	527.050	14.375	365.125
Motorcraft	20.750	527.050	15.000	381.000
Unipart TR7	20.813	528.638	14.125	358.775
GAZ GT4-2113	20.937	531.812	14.687	373.050
AVO TE137	21.000	533.400	13.500	342.900
Koni	21.000	533.400	14.875	377.825
Woodhead	21.000	533.400	15.250	387.350
Unipart (black) GDA 4109	21.125	536.575	15.000	381.000
Girling	21.125	536.575	15.375	390.525

Note: shock travel ratio is 1.51 x spring travel  
thus .250" shock travel = .165" spring travel

